


10-32 Jack (Female) Connector, Cable Entry: Clamp  
Center Conductor: Solder Attachment for RG178, RG196 DC-2GHz

## 1032-2D50-G178A / H1



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

**Interface**

According to N/A

**Electrical Data**Impedance 50 Ω  
Frequency DC to 2 GHz**Material And Plating**

Piece Parts	Material	Plating
Centre Contact	Phosphor Bronze	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Brass	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Insulator	PTFE	
Gasket	Silicone Rubber	Passivated

**Mechanical Data**Coupling Mechanisms Screw-Lock  
Mating Cycles ≥ 500  
Centre Contact Soldered  
Cable Entry Clamp**Environmental Data**Temperature Range -55°C to +155°C  
RoHS compliant**Packing**

Single or 100

**Weight**

N/A

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:-

Rosnol RF/Microwave Technology Co., Ltd.

[www.rosnol.com](http://www.rosnol.com); [info@rosnol.com](mailto:info@rosnol.com)

Phone: +886-3-463-5095 / Fax: +886-3-463-5952

N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/1