


**BMZ JACK (FEMALE) PIN CONTACT SIZE 8
ATTACHMENT FOR .085 FLEXIBLE COAX DC-40 GHz VSWR 1.4**

BMZ2EA50-0085A / 9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

MIL-STD-348B

Electrical Data

Impedance

50 Ω

Frequency

DC to 40 GHz

VSWR (Return Loss)

≤ 1.4 (≥ 15.6 dB)

Insertion Loss

≤ 0.06 x √F (GHz) dB

Insulation Resistance

≥ 5 GΩ

Test Voltage (at sea level)

1000 V rms

Material And Plating

Piece Parts	Material	Plating
Centre Contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Insulator	PTFE	
Gasket	Silicone Rubber	
Spring	Stainless Steel	Passivated

BMZ JACK (FEMALE) PIN CONTACT SIZE 8
ATTACHMENT FOR .085 FLEXIBLE COAX DC-40 GHz VSWR 1.4

BMZ2EA50-0085A / 9X

Mechanical Data

Coupling mechanisms	Push on
Mating Cycles	≥ 500
Engagement force	0.578 N
Disengagement force	3.34 N

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100