


2.92mm Plug (Male) Connector Solder/Solderless Contact Attachment
for .141, Cable, DC-40GHz VSWR1.2

K1E50-0141A / 91X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-35, IEEE Std 287-2007

Mechanically Compatible with

3.5mm and SMA

Electrical Data

Impedance

50 Ω

Frequency

DC to 40 GHz

VSWR (Return Loss)

≤ 1.20 (≥ 20.83 dB)

Insertion Loss

≤ 0.04 x √F (GHz) dB

Insulation Resistance

≥ 5 GΩ

Center Contact Resistance

≤ 3.0 mΩ

Outer Contact Resistance

≤ 2.0 mΩ

Test Voltage (at sea level)

750 V rms

Working Voltage (at sea level)

250 V rms

RF Leakage

≥ 100 dB up to 1 GHz

- limitations are possible due to the used cable type -

Material And Plating

Piece Parts	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Brass	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Insulator	PEI	
Barrel	Stainless Steel	Passivated

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:-

Date:
12/7/2020

Rosnol RF/Microwave Technology Co., Ltd.

www.rosnol.com; info@rosnol.com

Phone: +886-3-463-5095 / Fax: +886-3-463-5952

N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

2.92mm Plug (Male) Connector Solder/Solderless Contact Attachment
for .141, Cable, DC-40GHz VSWR1.2

K1E50-0141A / 91X

Mechanical Data

Coupling mechanisms	Screw Lock
Mating Cycles	≥ 500
Coupling Test Torque	1.7 Nm
Recommended Torque	0.9 Nm
Centre contact	Plug-in
Cable entry	Soldered

Environmental Data

Temperature Range	-55°C to +165°C
Thermal Shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100