


N Jack (Female) Straight Connector Crimp / Contact Pin Solder Attachment
for LMR-400, ROSNOL RNL-400, DC-6GHz, VSWR 1.3

N2C50-R400A / 9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 60169-16; MIL-STD-348B/304; CECC 22210; MIL-PRF-39012

Electrical Data

Impedance	50 Ω	
Frequency	DC to 6 GHz	
VSWR (Return Loss)	≤ 1.30 (≥ 17.69 dB)	
Insertion Loss	≤ 0.05 dB	
Insulation Resistance	≥ 5 GΩ	
Center Contact Resistance	≤ 1 mΩ	
Outer Contact Resistance	≤ 0.25 mΩ	
Working Voltage	500 V rms	
Power Handling (at 20 °C, sea level, VSWR 1.0)	≤ 1000 W @ 1 GHz	≤ 700 W @ 2 GHz

-VSWR in application depends decisive on cable assembly process-

Material And Plating

Piece Parts	Material	Plating
Centre contact	Beryllium Copper	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Crimp Ferrules	Brass	Copper-Tin-Zinc Alloy

**N Jack (Female) Straight Connector Crimp / Contact Pin Solder Attachment
for LMR-400, ROSNOL RNL-400, DC-6GHz, VSWR 1.3**

N2C50-R400A / 9X

Mechanical Data

Coupling Mechanisms	Screw-On
Mating Cycles	≥ 500
Coupling Nut Retention	≥ 450 N
Center Contact Captivation: axial	≥ 28 N
Coupling Test Torque	max. 1.7 Nm
Recommended Torque	0.7 Nm to 1.1 Nm
Centre Contact	Soldered
Cable Entry	Crimped

Environmental Data

Temperature Range	-65°C to +165°C
Thermal Shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106
RoHS	Compliant

Suitable Cables

LMR-400; RNL-400; Belden 7810A, 8214, 9913; Ecoflex 10

Packing

Single or 100