




Precision SMA Jack (Female) Connector Solder Attachment 4 Hole Flange Mount to
.141 Cable ,8.64mm (.340 inch) Hole Spacing DC-27GHz VSWR1.30

PCA2EBF50-EZ141A / 9X



Mounting Dimensions



	mm		inch	
	Max.	Min.	Max.	Min.
A	6.6	6.5	.260	.256
B	2.8	2.7	.110	.106
C	8.69	8.59	.342	.338

All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 60169-15; CECC 22110; MIL-PRF-39012; MIL-STD-348B/405

Electrical Data

Impedance	50 Ω
Frequency	DC to 27 GHz
VSWR (Return Loss)	≤ 1.30 (≥ 17.69dB)
Insertion Loss	≤ 0.03 x √F (GHz) dB
Insulation Resistance	≥ 5 GΩ
Center Contact Resistance	≤ 3 mΩ
Outer Contact Resistance	≤ 2 mΩ
Test Voltage	1000 V rms
Working Voltage (at sea level)	480 V rms
Power Handling (at 20 °C, sea level, VSWR 1.0)	≤ 200 W @ 2 GHz
-VSWR in application depends decisive on cable assembly process-	

Material And Plating

Piece Parts	Material	Plating
Centre contact	Beryllium Copper	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Barrel	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)

Precision SMA Jack (Female) Connector Solder Attachment 4 Hole Flange Mount to
.141 Cable ,8.64mm (.340 inch) Hole Spacing DC-27GHz VSWR1.30

PCA2EBF50-EZ141A / 9X

Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500
Centre Contact	Plug-in
Terminal Type	Cable solder
Captivated Type	Mechanical
Coupling nut retention	≥ 270 N
Center Contact Captivation: axial	≥ 27 N
Coupling Test Torque	max. 1.7 Nm
Recommended Torque	0.8 Nm to 1.1 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond.D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100