



 Fixed Attenuator plug/jack
 7/16 plug (male) / 7/16 jack (female)

FA-D1D25A-3G2W1/H44-H4



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-4

Electrical Data

Impedance

50 Ω

Frequency

DC to 3 GHz

VSWR (Return Loss)

≤ 1.25 (> 19.08 dB)

Power rating

2 Watt average power up to 25 °C

Maximum Deviation Over Frequency

Nominal ATTN (dB)	Deviation (dB)
1-10	±0.4
11-30	±0.5

Mechanical Data

Coupling mechanisms

Screw-lock

Weight

N/A

Environmental Data

Temperature range

-55°C to +130°C

RoHS

compliant

Material And Plating

Piece Parts (7/16)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating (Nickel underplated)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling Nut	Brass	Copper-Tin-Zinc Alloy
Piece Parts (7/16)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating (Nickel underplated)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	

Packing

Single or 100

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.-

 Rosnol RF/Microwave Technology
www.rosnol.com; info@rosnol.com

 Date:
 19/11/12

 Phone: +886-3-463-5095 / Fax: +886-3-463-5952
 N-CAGE Code: SFKKO

Page

1/1