


30 dB Fixed Attenuator, TNC Male Plug to TNC Female Jack Black Anodized
Aluminum Heatsink Body Rated to 10 Watts Up to 18 GHz

FA-PCT1PCT25A-18G10W30 / 9XX-9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

Precision TNC according to

IEC 60169-17; MIL-STD-348B/313

Electrical Data

Impedance

50 Ω

Frequency

DC to 18 GHz

VSWR (Return Loss)

≤ 1.4 (≥ 15.6 dB)

Insertion Loss

≤ 0.1 x √F (GHz) dB

Accuracy Of Attenuation & Power

Frequency	DC to 4 GHz	4 to 8 GHz	8 to 12.4 GHz	12.4 to 18 GHz
Deviation (± dB)	0.5	0.6	0.7	1.0

Material And Plating

Piece Parts	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Stainless Steel	Passivated
Piece Parts	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:-

Date:
6/23/2019

Rosnol RF/Microwave Technology Co., Ltd.

www.rosnol.com; info@rosnol.com

Phone: +886-3-463-5095 / Fax: +886-3-463-5952

N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

30 dB Fixed Attenuator, TNC Male Plug to TNC Female Jack Black Anodized
Aluminum Heatsink Body Rated to 10 Watts Up to 18 GHz

FA-PCT1PCT25A-18G10W30 / 9XX-9X

Mechanical Data

Coupling mechanisms	Screw-lock
Mating cycles	min. 500
Center Contact Captivation	≥ 27 N
Coupling test torque	max. 1.7 Nm
Recommended torque	0.46 Nm to 0.69 Nm

Environmental Data

Temperature Range	-65°C to +160°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition G
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100