


MCX Jack (female) Connector Solder Pin PCB
Through Holes Right Angle DC-6GHz, VSWR ≤ 1.20

MCX2I59-0940C / H1



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-36

Electrical Data

Impedance

50 Ω

Frequency

DC to 6 GHz

VSWR (Return Loss)

≤ 1.20 (≥ 20.83 dB)

Insertion Loss

$\leq 0.05 \times \sqrt{f}$ (GHz) dB

Insulation Resistance

≥ 1 G Ω

Center Contact Resistance

≤ 5.0 m Ω

Outer Contact Resistance

≤ 2.5 m Ω

Test Voltage (at sea level)

750 V rms

Working Voltage (at sea level)

335 V rms

Material And Plating

Piece Parts	Material	Plating
Centre Contact	Phosphor Bronze	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Brass	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Insulator	PTFE	

MCX Jack (female) Connector Solder Pin PCB
Through Holes Right Angle DC-6GHz, VSWR \leq 1.20

MCX2I59-0940C / H1

Mechanical Data

Coupling mechanisms	Snap-lock
Mating Cycles	\geq 500
Engagement Force	\leq 25 N
Disengagement Force	8 N min. to 20 N max.
Center Contact Captivation	\geq 10 N

Environmental Data

Temperature Range	-55°C to +155°C
Thermal shock	CECC 22 220, Chapter 4.6.7
Vibration	CECC 22 220, Chapter 4.6.3
Corrosion	CECC 22 220, Chapter 4.6.10
Moisture resistance	CECC 22 220, Chapter 4.6.6
RoHS	compliant

Packing

Single or 100