


2.92mm jack (female) Connector Solder Attachment 2 Hole Flange Mount
Stub Terminal, 8.9mm (.350 inch) Hole Spacing DC-40GHz VSWR1.20

K2GTA50-1230E / 9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-35

Mechanically compatible with

3.5mm and SMA

Electrical Data

Impedance

50 Ω

Frequency

DC to 40 GHz

VSWR (Return Loss)

≤ 1.20 (≥ 20.83 dB)

Insertion Loss

≤ 0.04 x √F (GHz) dB

Insulation Resistance

≥ 5 GΩ

Center contact resistance

≤ 3.0 mΩ

Outer contact resistance

≤ 2.0 mΩ

Test Voltage

750 V rms

Working Voltage (at sea level)

250 V rms

Power Handling

≤ 100 W @ 1 GHz

Material And Plating

Piece Parts

Material

Plating

Centre contact

Beryllium Copper

Gold plating, 3 µinch

Body

Stainless Steel

(Non-magnetic nickel-phosphorus underplating, 80 µinch)

Insulator

PEI/PTFE

Passivated

2.92mm jack (female) Connector Solder Attachment 2 Hole Flange Mount
Stub Terminal, 8.9mm (.350 inch) Hole Spacing DC-40GHz VSWR 1.20

K2GTA50-1230E / 9X

Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500
Centre Contact	Soldered
Terminal Type	Stub
Captivated Type	Mechanical Captivation
Center contact captivation	≥ 20 N
Coupling test torque	1.70 Nm
Recommended torque	0.80 Nm to 1.10 Nm
Recommended torque fastening screws	0.3 Nm

Environmental Data

Temperature Range	-55°C to +165°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100