


SMA Jack (Female) Connector Solder Attachment 4 Hole Flange Mount  
Microstrip Terminal, 8.64mm (.340 inch) Hole Spacing DC-18GHz VSWR 1.30

## SMA2GFE50-1080A-EC / 91



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

### Interface

According to

IEC 61169-15; MIL-STD-348B/310

### Electrical Data

Impedance

50 Ω

Frequency

DC to 18 GHz

VSWR (Return Loss)

≤ 1.30 (≥ 17.7 dB)

Insertion Loss

≤ 0.05 x √F (GHz) dB

Insulation Resistance

≥ 5 GΩ

Center Contact Resistance

≤ 3 mΩ

Outer Contact Resistance

≤ 2 mΩ

Test Voltage

1000 V rms

Working Voltage (at sea level)

480 V rms

Power Handling (at 20 °C, sea level, VSWR 1.0)

≤ 200 W @ 2 GHz

### Material And Plating

#### Piece Parts

#### Material

#### Plating

Centre contact

Beryllium Copper

Gold plating, 3 µinch  
(Non-magnetic nickel-phosphorus underplating, 80 µinch)

Body

Brass

Gold plating, 3 µinch  
(Non-magnetic nickel-phosphorus underplating, 80 µinch)

Insulator

PTFE

SMA Jack (Female) Connector Solder Attachment 4 Hole Flange Mount  
Microstrip Terminal, 8.64mm (.340 inch) Hole Spacing DC-18GHz VSWR1.30

SMA2GFE50-1080A-EC / 91

## Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500
Centre Contact	Soldered
Terminal Type	Microstrip
Captivated Type	Epoxy Captivation
Center Contact Captivation: axial	≥ 27 N
	≥ 3 Ncm
radial	
Coupling Test Torque	max. 1.7 Nm
Recommended Torque	0.8 Nm to 11 Nm

## Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond.D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	compliant

## Packing

Single or 100