


SMA Straight Panel Receptacle Jack
(Semicircular End)

SMA2GTC50-1700C/9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to MIL-C-39012;MIL-STD-348A/310

Electrical Data

Impedance 50 Ω
Frequency DC to 18 GHz
VSWR (Return Loss) ≤ 1.30 (≥ 17.69 dB)
Insertion Loss $\leq 0.05 \times \sqrt{F} \text{ (GHz)}$ dB

Mechanical Data

Coupling mechanisms Screw-lock
Weight 0.0024 kg

Environmental Data

Temperature range -65°C to +165°C
RoHS compliant

Material And Plating

Piece Parts	Material	Plating
Centre contact	Beryllium Copper	Gold plating(Nickel underplated)
Body	Stainless Steel	Passivated
Insulator	PTFE	

Packing

Single or 100

Related Document

Mounting Dimension MD120

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only.. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:-

Date:
19/11/10

Rosnol RF/Microwave Technology

www.rosnol.com ; info@rosnol.com

Phone:+886-3-463-5095

Fax:+886-3-463-5952

Page

1/1