


Precision SMA Jack (Female) Field Replaceable Connector with EMI Gasket  
2 Hole Flange Mount .400 Hole Spacing, .018 inch Accept Pin DC-27GHz VSWR1.15

**PCA2BT50-0018B-EMI / 9X**



| P/N                   | Accept Pin<br>mm [inch] | Max. Pin Depth<br>mm [inch] | Ø A<br>mm [inch] |
|-----------------------|-------------------------|-----------------------------|------------------|
| PCA2BT50-0020B-EMI/9X | 0.51 [.020]             | 2.54 [.100]                 | 2.67 [.105]      |
| PCA2BT50-0018B-EMI/9X | 0.46 [.018]             | 2.54 [.100]                 | 2.59 [.102]      |
| PCA2BT50-0015B-EMI/9X | 0.38 [.015]             | 2.54 [.100]                 | 1.96 [.077]      |
| PCA2BT50-0012B-EMI/9X | 0.30 [.012]             | 1.90 [.075]                 | 1.96 [.077]      |
| PCA2BT50-0009B-EMI/9X | 0.23 [.009]             | 1.65 [.065]                 | 1.52 [.060]      |

All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

**Interface**

According to

IEC 60169-15; MIL-STD-348B/310

**Electrical Data**

Impedance

50 Ω

Frequency

DC to 27 GHz

VSWR (Return Loss)

≤ 1.15 (≥ 23.13 dB)

Insertion Loss

≤ 0.04 x √F (GHz) dB

Insulation Resistance

≥ 5 GΩ

Center Contact Resistance

≤ 3.0 mΩ

Outer Contact Resistance

≤ 2.0 mΩ

Test Voltage

1000 V rms

Working voltage

480 V rms

Power handling

≤ 200 W @ 2 GHz

RF-leakage

≥ 100 dB up to 1 GHz

**Material And Plating**

| Piece Parts    | Material                      | Plating                                                                          |
|----------------|-------------------------------|----------------------------------------------------------------------------------|
| Centre Contact | Beryllium Copper              | Gold plating, 3 μinch<br>(Non-magnetic nickel-phosphorus underplating, 80 μinch) |
| Body           | Stainless Steel               | Passivated                                                                       |
| Insulator      | PTFE                          |                                                                                  |
| EMI Gasket     | Conductive Silicone Elastomer |                                                                                  |

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:  
Date: JUL/16/2021

Rosnol RF/Microwave Technology Co., Ltd.  
[www.rosnol.com](http://www.rosnol.com); [info@rosnol.com](mailto:info@rosnol.com)  
Phone: +886-3-463-5095 / Fax: +886-3-463-5952  
N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

Precision SMA Jack (Female) Field Replaceable Connector with EMI Gasket  
2 Hole Flange Mount .400 Hole Spacing, .012 inch Accept Pin DC-27GHz VSWR1.15

## PCA2BT50-0012B-EMI / 9X

### Mechanical Data

|                                   |                   |
|-----------------------------------|-------------------|
| Coupling mechanisms               | Screw-lock        |
| Mating Cycles                     | ≥ 500             |
| Captivated Type                   | Mechanical        |
| Center Contact Captivation: axial | ≥ 27 N            |
| Coupling Test Torque              | 1.70 Nm           |
| Recommended Torque                | 0.80 Nm to 1.1 Nm |

### Environmental Data

|                     |                                 |
|---------------------|---------------------------------|
| Temperature Range   | -65°C to +165°C                 |
| Thermal shock       | MIL-STD-202, Meth. 107, Cond. B |
| Corrosion           | MIL-STD-202, Meth. 101, Cond. B |
| Vibration           | MIL-STD-202, Meth. 204, Cond.D  |
| Shock               | MIL-STD-202, Meth. 213, Cond. I |
| Moisture Resistance | MIL-STD-202, Meth. 106          |
| RoHS                | compliant                       |

### Packing

Single or 100