


Precision SMA Jack (Female) Field Replaceable Connector with EMI
Gasket 2 Hole Flange Mount .481 Hole Spacing, .036 inch Accept
Pin DC-27GHz VSWR1.15

PCA2BT50-0036A-EMI / 9X



P/N	Accept Pin mm [inch]	Max. Pin Depth mm [inch]	Ø A mm [inch]
PCA2BT50-0036A-EMI/9X	0.91 [.036]	2.54 [.100]	3.91 [.154]
PCA2BT50-0020A-EMI/9X	0.51 [.020]	2.54 [.100]	2.67 [.105]
PCA2BT50-0018A-EMI/9X	0.46 [.018]	2.54 [.100]	2.59 [.102]
PCA2BT50-0015A-EMI/9X	0.38 [.015]	2.54 [.100]	1.96 [.077]
PCA2BT50-0012A-EMI/9X	0.30 [.012]	1.90 [.075]	1.96 [.077]
PCA2BT50-0009A-EMI/9X	0.23 [.009]	1.65 [.065]	1.52 [.060]

All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 60169-15; MIL-STD-348B/310

Electrical Data

Impedance	50 Ω
Frequency	DC to 27 GHz
VSWR (Return Loss)	≤ 1.15 (≥ 23.13 dB)
Insertion Loss	≤ 0.04 x √F (GHz) dB
Insulation Resistance	≥ 5 GΩ
Center Contact Resistance	≤ 3.0 mΩ
Outer Contact Resistance	≤ 2.0 mΩ
Test Voltage	1000 V rms
Working voltage	480 V rms
Power handling	≤ 200 W @ 2 GHz
RF-leakage	≥ 100 dB up to 1 GHz

Material And Plating

Piece Parts	Material	Plating
Centre Contact	Beryllium Copper	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
EMI Gasket	Conductive Silicone Elastomer	

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:
Date:
JUL/16/2021

Rosnol RF/Microwave Technology Co., Ltd.
www.rosnol.com; info@rosnol.com
Phone: +886-3-463-5095 / Fax: +886-3-463-5952
N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

Precision SMA Jack (Female) Field Replaceable Connector with EMI
Gasket 2 Hole Flange Mount .481 Hole Spacing, .036 inch Accept Pin
DC-27GHz VSWR1.15

PCA2BT50-0036A-EMI / 9X

Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500
Captivated Type	Mechanical
Center Contact Captivation: axial	≥ 27 N
Coupling Test Torque	1.70 Nm
Recommended Torque	0.80 Nm to 1.1 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100