


SMA plug (male) / BNC plug (male) Adapter
DC-6 GHz VSWR1.2

AD-A1B15A / 9XX-9XX



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

SMA side according to

IEC 60169-15; MIL-STD-348B/310

BNC side according to

MIL-STD-348B/301

Electrical Data

Impedance

50 Ω

Frequency

DC to 6 GHz

VSWR (Return Loss)

DC-4 GHz: ≤ 1.15 (≥ 23.13 dB)

4-6 GHz: ≤ 1.2 (≥ 20.83 dB)

Insertion Loss

$\leq 0.05 \times \sqrt{f}$ (GHz) dB

Insulation Resistance

≥ 5 G Ω

Center contact resistance

≤ 3 m Ω , SMA side

≤ 1.5 m Ω , BNC side

Outer contact resistance

≤ 2 m Ω , SMA side

≤ 1.0 m Ω , BNC side

Test Voltage (at sea level)

1000 V rms

Working Voltage (at sea level)

400 V rms

RF Leakage

≤ 80 W @ 2 GHz

Material And Plating

Piece Parts (SMA)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Stainless Steel	Passivated
Piece Parts (BNC)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Stainless Steel	Passivated

SMA plug (male) / BNC plug (male) Adapter
DC-6 GHz VSWR1.2

AD-A1B15A / 9XX-9XX

Mechanical Data

Coupling Mechanisms	SMA Side	BNC Side
Mating Cycles	Screw-lock	Bayonet-lock
Center Contact Captivation	min. 500	min. 500
Coupling test torque	≥ 27 N	≥ 27 N
Coupling test torque	max. 1.7 Nm	N/A
	0.8 Nm to 1.1 Nm	N/A

Environmental Data

Temperature Range	-65°C to +165°C
Thermal Shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100