
ROSNOL® RF/Microwave Interconnect

Technical Data Sheet

SMA Plug (Male) to Precision N Plug (Male) Straight Adapter, DC-18 GHz, VSWR 1.15

AD-A1PCN15B / 133-133



All dimensions are in mm [inch]
Tolerances according to DIN ISO 2768-mH

Interface

SMA According to	IEC 60169-15, CECC22110, MIL-PRF-39012, MIL-STD-348B/310, EN 122110
Precision N According to	IEC 61169-16, MIL-STD 348B/402, IEEE Std 287, MIL-PRF-39012

Electrical Data

Impedance	50 Ω	
Frequency	DC to 18 GHz	
VSWR (Return Loss)	≤ 1.15 (≥ 23.13 dB)	
Insertion Loss	≤ 0.05 x √F (GHz) dB	
Insulation Resistance	≥ 5 GΩ	
Center Contact Resistance	≤ 3 mΩ, SMA side	≤ 1 mΩ, Precision N side
Outer Contact Resistance	≤ 2 mΩ, SMA side	≤ 0.25 mΩ, Precision N side
Test Voltage	1000 V rms	
Working Voltage	480 V rms	
RF-leakage	≥ 90 dB up to 1 GHz	

Material and Plating

Piece Parts (SMA)	Material	Plating
Centre Contact	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling Nut	Brass	Nickel

Piece Parts (Precision N)	Material	Plating
Centre Contact	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling Nut	Brass	Nickel

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rosnol RF/Microwave Technology Co., Ltd.
www.rosnol.com; info@rosnol.com
Phone: +886-3-463-5095 / Fax: +886-3-463-5952
N-CAGE Code: SFKK0 / ISO9001 Certified

SMA Plug (Male) to Precision N Plug (Male) Straight Adapter, DC-18 GHz, VSWR 1.15

AD-A1PCN15B / 133-133

Mechanical Data

	SMA side	Precision N side
Coupling Mechanisms	Screw-On	Screw-On
Mating Cycles	min. 500	min. 500
Center Contact Captivation: axial	≥ 28 N	≥ 28 N
Coupling Test Torque	max. 1.70 Nm	max. 1.70 Nm
Recommended Torque	0.57 Nm	1.0 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal Shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	Compliant

Packing

Single or 100

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rosnol RF/Microwave Technology Co., Ltd.
www.rosnol.com; info@rosnol.com
Phone: +886-3-463-5095 / Fax: +886-3-463-5952
N-CAGE Code: SFKK0 / ISO9001 Certified