


SMA plug (male) / Precision TNC jack (female)
Straight adaptor DC-18GHz VSWR 1.20

AD-A1PCT25B / 933-93



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

SMA according to

IEC 60169-15; MIL-STD-348A/310

Precision TNC according to

IEC 60169-26; MIL-STD-348A/313

Electrical Data

Impedance

50 Ω

Frequency

DC to 18 GHz

VSWR (Return Loss)

≤ 1.20 (≥ 20.8 dB)

Insertion Loss

$\leq 0.05 \times \sqrt{F}$ (GHz) dB

Insulation resistance

≥ 5 G Ω

Center contact resistance

≤ 3.0 m Ω , SMA side;

≤ 1.5 m Ω , Precision TNC side

Outer contact resistance

≤ 2.0 m Ω , SMA side;

≤ 1.0 m Ω , Precision TNC side

Test voltage

1000 V rms

Working voltage

480 V rms

RF-leakage

≥ 90 dB up to 1 GHz

Material And Plating

Piece Parts (SMA)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone rubber	
Coupling nut	Brass	Nickel
Piece Parts (Precision TNC)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Brass	Nickel
Insulator	PTFE	

SMA plug (male) / Precision TNC jack (female) Straight adaptor DC-18GHz VSWR 1.20

AD-A1PCT25B / 933-93

Mechanical Data

	SMA side	Precision TNC side
Coupling mechanisms	Screw-lock	Screw-lock
Mating cycles	min. 500	min. 500
Center contact captivation: axial	≥ 27 N	≥ 27 N
Coupling test torque	max. 1.7 Nm	max. 1.7 Nm
Recommended torque	0.80 Nm to 1.10 Nm	0.46 Nm to 0.69 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100