


SMA plug (male) / TNC jack (female) Adaptors Straight DC-11 GHz VSWR1.20

AD-A1T25B / 133-13



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

SMA according to

IEC 60169-15; MIL-STD-348B/310

TNC according to

IEC 60169-17; MIL-STD-348B/313

Electrical Data

Impedance

50 Ω

Frequency

DC to 11 GHz

VSWR (Return Loss)

≤ 1.20 (≥ 20.83 dB)

Insertion Loss

≤ 0.03 x √F (GHz) dB

Insulation Resistance

≥ 5 GΩ

Center Contact Resistance

≤ 3 mΩ, SMA side

≤ 1.5 mΩ, TNC side

Outer Contact Resistance

≤ 2 mΩ, SMA side

≤ 1 mΩ, TNC side

Test Voltage

1000 V rms

Working Voltage (at sea level)

480 V rms

Power Handling (at 20 °C, sea level, VSWR 1.0)

≤ 80 W @ 2 GHz

Dielectric withstanding Voltage

1500 V min

RF leakage

< -50dB @ 2GHz, < -45 dB @ 8GHz

Material And Plating

Piece Parts (SMA)	Material	Plating
Centre contact	Brass	Gold plating, 3 pinch (Non-magnetic nickel-phosphorus underplating, 80 pinch)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Brass	Nickel
Piece Parts (TNC)	Material	Plating
Centre contact	Brass	Gold plating, 3 pinch (Non-magnetic nickel-phosphorus underplating, 80 pinch)
Body	Brass	Nickel
Insulator	PTFE	

SMA plug (male) / TNC jack (female) Adaptors Straight DC-11 GHz VSWR1.20

AD-A1T25B / 133-13

Mechanical Data

	SMA side	TNC side
Coupling mechanisms	Screw-lock	Screw-lock
Mating Cycles	min. 500	min. 500
Coupling nut retention	≥ 27 N	N/A
Center Contact Captivation: axial	≥ 3 Ncm	≥ 27 N
Coupling Test Torque	1.7 Nm max.	max. 1.7 Nm
Recommended Torque	0.9 Nm	0.46 Nm to 0.69 Nm

Environmental Data

Temperature Range	-65°C to +155°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond.D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100