


BNC jack (female) / SSMB jack (female) Straight adaptor
DC- 4GHz VSWR1.35

AD-B2SB25A / 94-91



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

BNC according to IEC 60169-8; MIL-STD-348B/301
SMB according to IEC 60169-10; MIL-STD-348B/311

Electrical Data

Impedance 50 Ω
Frequency DC to 4 GHz
VSWR (Return Loss) ≤ 1.35 (≥ 16.54 dB)
Insertion Loss $\leq 0.05 \times \sqrt{F}$ (GHz) dB
Center contact resistance ≤ 1.5 m Ω , BNC side; ≤ 5 m Ω , SMB
Outer contact resistance ≤ 1 m Ω , BNC side; ≤ 2.5 m Ω , SMB

Material And Plating

Piece Parts (BNC)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	
Piece Parts (SMB)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Brass	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Insulator	PTFE	

BNC jack (female) / SSMB jack (female) Straight adaptor DC-4GHz VSWR1.35

AD-B2SB25A / 94-91

Mechanical Data

	BNC side	SSMB side
Coupling mechanisms	Bayonet-lock	Snap-lock
Mating cycles	min. 500	min. 500
Center contact captivation: axial	≥ 15 N	≥ 10 N
Coupling test torque	N/A	≤ 63 N
Recommended torque	N/A	8 N min. to 63 N max.

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100