


FME jack (female) / FME jack (female) Adaptors Straight DC-2.5GHz VSWR1.25

AD-E2E25C / H4-H4



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

N/A

Electrical Data

Impedance	50 Ω
Frequency	DC to 2.5 GHz
VSWR (Return Loss)	≤ 1.25 (≥ 19 dB)
Insertion Loss	≤ 0.1 x √F (GHz) dB
Insulation resistance	≥ 5 GΩ
Center contact resistance	≥ 10 mΩ
Outer contact resistance	≥ 5 mΩ
Test voltage	1000 V rms
Working voltage	500 V rms

Material And Plating

Piece Parts (FME)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	
Piece Parts (FME)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	

FME jack (female) / FME jack (female) Adaptors Straight DC-2.5GHz VSWR1.25

AD-E2E25C / H4-H4

Mechanical Data

Coupling Mechanisms	Screw-lock
Mating Cycles	≥ 300
Coupling torque recommended	≥ 2 Nm

Environmental Data

Temperature Range	-55°C to +125°C
Corrosion	MIL-STD-202, Method 101
Vibration	MIL-STD-202, Method 204
RoHS	compliant

Packing

Single or 100