


2.92mm Jack (Female) to 2.92mm Jack (Female)
Panel 4 Hole Flange Mount Adapte DC-40 GHz, VSWR \leq 1.20

AD-K2K25A-PF / 9X-9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-35; IEEE Std 287

Electrical Data

Impedance

50 Ω

Frequency

DC to 40 GHz

VSWR (Return Loss)

\leq 1.20 ($>$ 20.83 dB)

Insertion Loss

\leq 0.04 \times \sqrt{f} (GHz) dB

Insulation resistance

\geq 5 G Ω

Proof voltage (at sea level)

750 V rms

Working voltage (at sea level)

250 V rms

RF-leakage

\geq 100 dB up to 1 GHz

Power Handling

20W

Material And Plating

Piece Parts (2.92mm)	Material	Plating
Centre contact	Beryllium Copper	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Stainless Steel	Passivated
Insulator	PEI	
Piece Parts (2.92mm)	Material	Plating
Centre contact	Beryllium Copper	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Stainless Steel	Passivated
Insulator	PEI	

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:-
Date:
JUL/16/2021

Rosnol RF/Microwave Technology Co., Ltd.

www.rosnol.com; info@rosnol.com

Phone: +886-3-463-5095 / Fax: +886-3-463-5952

N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

2.92mm Jack (Female) to 2.92mm Jack (Female)
Panel 4 Hole Flange Mount Adapte DC-40 GHz, VSWR \leq 1.20

AD-K2K25A-PF / 9X-9X

Mechanical Data

Coupling mechanisms	Screw-lock
Mating cycles	\geq 500
Center contact captivation	\geq 20 N
Coupling test torque	1.70 Nmm
Recommended torque	0.80 Nm to 1.10 Nm

Environmental Data

Temperature Range	-65 °C to +165 °C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100