


3.5mm jack (female) / Precision SMA jack (female)
Adapter Straight DC-27 GHz VSWR1.15

AD-PC2PCA25A / 9X-9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

3.5mm according to
Precision SMA according to

IEC 60169-23
IEC 60169-15; MIL-STD-348A/310

Electrical Data

Impedance	50 Ω
Frequency	DC to 27 GHz
VSWR (Return Loss)	≤ 1.15 (≥ 23.13 dB)
Insertion Loss	≤ 0.05 $\times \sqrt{F}$ (GHz) dB
Insulation resistance	≥ 5 GΩ
Test voltage	1000 V rms
RF-leakage	≥ 100 dB up to 1 GHz

Material And Plating

Piece Parts (3.5mm)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PS	
Piece Parts (Precision SMA)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	

3.5mm jack (female) / Precision SMA jack (female)
Adapter Straight DC-27 GHz VSWR1.15

AD-PC2PCA25A / 9X-9X

Mechanical Data

Coupling mechanisms	3.5mm side	Precision SMA side
Mating Cycles	Screw-lock	Screw-lock
Center contact captivation	≥ 500	≥ 500
Coupling test torque	≥ 28 N	≥ 27 N
Recommended Torque	1.70 Nm	max. 1.7 Nm
	0.80 Nm to 1.10 Nm	0.8 Nm to 1.1 Nm

Environmental Data

Temperature Range	-65°C to +125°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 204, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture Resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100