



Precision N plug (male) / SMA jack (female)
4-Hole Panel Adapter, DC-18 GHz, VSWR ≤ 1.15

AD-PCN1A25A-PF / HXX-9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

N according to

IEC 61169-16; MIL-STD-348B/304

SMA according to

IEC 60169-15; MIL-STD-348B/310

Electrical Data

Impedance

50 Ω

Frequency

DC to 18 GHz

VSWR (Return Loss)

≤ 1.15 (≥ 23.1 dB)

Insertion loss

≤ 0.1 dB × √F (GHz) dB

Insulation resistance

≥ 5 GΩ

Test voltage (at sea level)

1000 V rms

Working voltage (at sea level)

480 V rms

RF-leakage

≥ 90 dB up to 1 GHz

Material And Plating

Piece Parts (Precision N)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating, 3 pinch (Non-magnetic nickel-phosphorus underplating, 80 pinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Stainless Steel	Passivated
Piece Parts (SMA)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 pinch (Non-magnetic nickel-phosphorus underplating, 80 pinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Gasket	Silicone Rubber	

Precision N plug (male) / SMA jack (female)
4-Hole Panel Adapter, DC-18 GHz, VSWR ≤ 1.15

AD-PCN1A25A-PF / HXX-9X

Mechanical Data

	Precision N side	SMA side
Coupling mechanisms	Screw-lock	Screw-lock
Mating cycles	≥ 500	≥ 500
Center contact captivation	≥ 28 N	≥ 28 N
Coupling test torque	1.70 Nm	1.70 Nm
Recommended torque	0.70 Nm to 1.10 Nm	0.80 Nm to 1.10 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	IEC 61169-1, Subclause 9.4.4
Corrosion	IEC 61169-1, Subclause 9.4.6
Vibration	IEC 61169-1, Subclause 9.3.3
Shock	IEC 61169-1, Subclause 9.3.14
Moisture resistance	IEC 61169-1, Subclause 9.4.3
RoHS	compliant

Packing

Single or 100