


Precision N jack (female) / 4.3-10 jack (female)
Straight Adaptor DC-12 GHz VSWR ≤ 1.13

AD-PCN2431025A / 94-94



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

Precision N according to

IEC 60169-16; MIL-STD-348B/402

4.3/10 according to

IEC 61169-54

Electrical Data

Impedance

50 Ω

Frequency

DC to 12 GHz

VSWR (Return Loss)

≤ 1.13 (≥ 24.3 dB)

Insertion Loss

≤ 0.04 × √F (GHz) dB

Mechanical Data

Coupling mechanisms

Precision N side

4.3/10 side

Mating cycles

Screw-lock

Screw-lock

Maximum torque

min. 500

min. 100

Recommended torque

1.70 Nm

5 Nm

Gauge

1.10 Nm

2 Nm

5.18 mm to 5.26 mm

3.10 mm to 3.20 mm

Environmental Data

Temperature Range

-65°C to +165°C

RoHS

compliant

Material And Plating

Piece Parts (Precision N)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	
Piece Parts (4.3-10)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	

Packing

Singleor 100