




Precision N Jack (Female) to Precision N Jack (Female)
Panel 4 Hole Flange Mount Adapter DC-18GHz VSWR1.20

AD-PCN2PCN25A-PF / H4-H4

MOUNTING DIMENSIONS



	mm		inch	
	MAX.	MIN.	MAX.	MIN.
A	16.3	16.1	.642	.634
B	3.6	3.5	.142	.138
C	18.35	18.15	.722	.715

All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-16, MIL-STD-348B/304

Electrical Data

Impedance	50 Ω
Frequency	DC to 18 GHz
VSWR (Return Loss)	≤ 1.20 (≥ 20.8 dB)
Insertion Loss	≤ 0.05 × √F (GHz) dB
Insulation Resistance	≥ 5 GΩ
Center contact resistance	≤ 1.0 mΩ
Outer contact resistance	≤ 1.0 mΩ
Test voltage	2500 V rms
Working voltage	1000 V rms
RF Leakage	≥ 128 dB up to 1 GHz

Material And Plating

Piece Parts (Precision N)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	
Piece Parts (Precision N)	Material	Plating
Centre contact	Phosphor Bronze	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	

Precision N Jack (Female) to Precision N Jack (Female)
Panel 4 Hole Flange Mount Adapter DC-18GHz VSWR1.20

AD-PCN2PCN25A-PF / H4-H4

Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500N
Center Contact Captivation: axial	≥ 28 N
Coupling Test Torque	max. 1.7 Nm
Recommended Torque	0.70Nm to 1.0 Nm

Environmental Data

Temperature Range	-55°C to +155°C
Thermal shock	IEC 61169-1, Subclause 9.4.4
Corrosion	IEC 61169-1, Subclause 9.4.6
Vibration	IEC 61169-1, Subclause 9.3.3
Shock	IEC 61169-1, Subclause 9.3.14
Moisture Resistance	IEC 61169-1, Subclause 9.4.3
RoHS	compliant

Packing

Single or 100