


Precision TNC Plug (Male) to Precision TNC Plug (Male), Straight Adapter,
DC - 18 GHz, VSWR 1.35

AD-PCT1PCT15B / 133-133



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 61169-26; CECC 22200; MIL-PRF-39012; MIL-STD-348B/406

Electrical Data

Impedance	50 Ω
Frequency	DC to 18 GHz
VSWR (Return Loss)	≤ 1.35 (≥ 16.54 dB)
Insertion Loss	≤ 0.06 x √F (GHz) dB
Insulation Resistance	≥ 5 G Ω
Center Contact Resistance	≤ 1.5 mΩ
Outer Contact Resistance	≤ 1 mΩ
Test Voltage	1500 V rms
Working Voltage	500 V rms

Material And Plating

Piece Parts (Precision TNC)	Material	Plating
Centre Contact	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Brass	Nickel
Piece Parts (Precision TNC)	Material	Plating
Centre Contact	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Brass	Nickel

Precision TNC Plug (Male) to Precision TNC Plug (Male), Straight Adapter,
DC - 18 GHz, VSWR 1.35

AD-PCT1PCT15B / 133-133

Mechanical Data

Coupling Mechanisms	Screw-On
Mating Cycles	≥ 500
Center Contact Captivation: axial	≥ 15 N
Coupling Test Torque	max. 1.7 Nm
Recommended Torque	0.46 Nm to 0.69 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal Shock	MIL-STD-202, Method 107, Cond. B
Corrosion	MIL-STD-202, Method 101, Cond. B
Vibration	MIL-STD-202, Method 204, Cond. B
Shock	MIL-STD-202, Method 213, Cond. G
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100