


SMP Full Detent plug (male) / Precision SMA (female)
Straight Adaptor DC-27 GHz, VSWR ≤ 1.15

AD-PF1PCA25A / 9X-9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

SMP (Full Detent) according to
Precision SMA according to

MIL-STD-348B/326
IEC 60169-15; MIL-STD-348B/310

Electrical Data

Impedance	50 Ω	
Frequency	DC to 27 GHz	
VSWR (Return Loss)	≤ 1.15 (> 23.1 dB)	
Insertion Loss	≤ 0.05 x √F (GHz) dB	
Insulation resistance	≥ 5 GΩ	
Center contact resistance	≤ 6.0 mΩ, SMP side;	≤ 3 mΩ, Precision SMA side
Outer contact resistance	≤ 2.0 mΩ, SMP side;	≤ 2 mΩ, Precision SMA side
Test voltage	500 V rms	
Working voltage	335 V rms	
Contact Current	1.2A DC max.	

Material And Plating

Piece Parts (SMP)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Piece Parts (Precision SMA)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	

**SMP Full Detent plug (male) / Precision SMA (female)
Straight Adaptor DC-27 GHz, VSWR ≤ 1.15**

AD-PF1PCA25A / 9X-9X

Mechanical Data

	SMP side	Precision SMA side
Coupling mechanisms	Snap-on	Screw-lock
Mating cycles	≥ 100	min. 500
Center contact captivation: axial	≥ 27 N	≥ 27 N
Engagement force		
- Full detent	≤ 68 N max.	None
Disengagement force		
- Full detent	≥ 22 N min.	None
Coupling test torque	N/A	max. 1.7 Nm
Recommended torque	N/A	0.8 Nm to 1.1 Nm

Environmental Data

Temperature Range	-65°C to +155°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition A
Moisture resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100