




4 Hole Flange Mount SMPM Plug (Male) to SMA Jack (Female)
6.35 (.250 inch) Hole Spacing DC-26.5 GHz VSWR 1.08

AD-PMF1A25A-PF / 9X-9X



Mounting Dimensions



	mm		inch	
	Max.	Min.	Max.	Min.
A	6.4	6.3	0.252	0.248
B	2.56	2.46	0.101	0.097
C	9.57	9.47	0.376	0.372

All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

SMPM side according to

MIL-STD-348B/328

SMA side according to

IEC 61169-15

Electrical Data

Impedance

50 Ω

Frequency

DC to 26.5 GHz

VSWR (Return Loss)

≤ 1.08 + 0.10 x FGHz

Insertion Loss

≤ 0.1 x √F (GHz) dB

Insulation resistance

≥ 5 GΩ

Voltage Rating

≤ 150 VRMS

Center contact resistance

≤ 6 mΩ

Outer contact resistance

≤ 2 mΩ

Material And Plating

Piece Parts (SMPM)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Stainless Steel	Passivated
Insulator	PEI	
Piece Parts (2.92mm)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μinch (Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Stainless Steel	Passivated
Insulator	PEI	

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:
Date: 6/23/2019

Rosnol RF/Microwave Technology Co., Ltd.
www.rosnol.com; info@rosnol.com
Phone: +886-3-463-5095 / Fax: +886-3-463-5952
N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

4 Hole Flange Mount SMPM Plug (Male) to SMA Jack (Female)
6.35 (.250 inch) Hole Spacing DC-26.5 GHz VSWR 1.08

AD-PMF1A25A-PF / 9X-9X

Mechanical Data

Coupling mechanisms	SMPM (Full detent) Side	2.92mm Side
Mating Cycles	Snap-on	Screw-lock
Center contact captivation axial	≥ 100	min. 500
Coupling test torque	≥ 7 N	≥ 20 N
Recommended torque	N/A	1.70 Nm
Engagement force	N/A	0.80 Nm to 1.10 Nm
Disengagement force	19 N max.	N/A
	29 N min.	N/A

Environmental Data

Temperature Range	-55°C to +165°C
RoHS	compliant

Packing

Single or 100