


2.4mm Plug (Male) to Precision SMA Jack (Female) Adapter
DC-27GHz VSWR1.15

AD-Q1PCA25A / 9XX-9X



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

Mechanically compatible with
According to

2.4mm Side
1.85mm
IEC 61169-40, IEEE Std 287

Precision SMA Side
2.92mm and 3.5mm
IEC 60169-15, MIL-STD-348B/310

Electrical Data

Impedance	50 Ω
Frequency	DC to 27 GHz
VSWR (Return Loss)	≤ 1.15 (≥ 23.13 dB)
Insertion Loss	≤ 0.05 x √F (GHz) dB
Insulation Resistance	≥ 5 GΩ
Center Contact Resistance 2.4mm	≤ 4 mΩ
Outer Contact Resistance 2.4mm	≤ 2.5 mΩ
Center Contact Resistance Precision SMA	≤ 3 mΩ
Outer Contact Resistance Precision SMA	≤ 2 mΩ
Test Voltage (at sea level)	500 V rms
Working Voltage (at sea level)	150 V rms
RF Leakage	≥ 100 dB up to 1 GHz

Material And Plating

Piece Parts (2.4mm)	Material	Plating
Centre Contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PEI	
Gasket	Silicone Rubber	
Coupling Nut	Stainless Steel	Passivated
Piece Parts (Precision SMA)	Material	Plating
Centre Contact	Beryllium Copper	Gold plating, 3 µinch (Non-magnetic nickel-phosphorus underplating, 80 µinch)
Body	Stainless Steel	Passivated
Insulator	PTFE	

2.4mm Plug (Male) to Precision SMA Jack (Female) Adapter
DC-27GHz VSWR1.15

AD-Q1PCA25A / 9XX-9X

Mechanical Data

Coupling mechanisms	2.4mm Side	Precision SMA Side
Mating Cycles	Screw-lock	Screw-lock
Coupling Nut Retention	≥ 500	≥ 500
Center Contact Captivation	≥ 270 N	≥ 270 N
Coupling Test Torque	≥ 20 N	≥ 20 N
Recommended Torque	1.65 Nm max.	1.70 Nm max.
	0.9 Nm	0.9 Nm

Environmental Data

Temperature Range	-55°C to +165°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Standard	Single
Weight	N/A