


QN Plug (Male) / N Jack (Female) Adaptors Straight DC-6 GHz VSWR1.2

AD-QN1N25A / 944-94



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

QN according to

IEC 61169-42

N according to

IEC 60169-16; MIL-STD-348B/304; CECC 22210; MIL-PRF-39012

Electrical Data

Impedance

50 Ω

Frequency

DC to 6 GHz

Insertion Loss

≤ 1.2 (≥ 20.83 dB)

Insertion loss

≤ 0.05 × √F (GHz) dB

Insulation resistance

≥ 5 GΩ

Center contact resistance

≤ 1.5 mΩ, QN side

≤ 1 mΩ, N side

Outer contact resistance

≤ 1.5 mΩ, QN side

≤ 0.25 mΩ, N side

Working voltage

1000 V rms

Test voltage

2500 V rms

Power handling

300 W @ 2.5 GHz (typ.)

Material And Plating

Piece Parts (QN)

Material

Plating

Centre contact

Beryllium Copper

Gold plating

(Non-magnetic nickel-phosphorus underplating)

Body

Brass

Copper-Tin-Zinc Alloy

Insulator

PTFE

Gasket

Silicone Rubber

Coupling nut

Brass

Copper-Tin-Zinc Alloy

Piece Parts (N)

Material

Plating

Centre contact

Beryllium Copper

Gold plating

(Non-magnetic nickel-phosphorus underplating)

Body

Brass

Copper-Tin-Zinc Alloy

Insulator

PTFE

QN Plug (Male) / N Jack (Female) Adaptors Straight DC-6 GHz VSWR1.2

AD-QN1N25A / 944-94

Mechanical Data

	QN side	N side
Coupling Mechanisms	Quick-lock	Screw-lock
Mating Cycles	min. 100	min. 500
Center contact captivation: axial	≥ 28 N	≥ 28 N
Engagement force	30 N (typ.)	N/A
Disengagement force	30 N (typ.)	N/A
Coupling test torque	N/A	max. 1.7 Nm
Recommended torque	N/A	0.7 Nm to 1.1 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Method 107 D, Condition B
Corrosion	MIL-STD-202, Method 101 D, Condition B
Vibration	MIL-STD-202, Method 204 D, Condition A
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106 F
RoHS	compliant

Packing

Single or 100