


1.85mm plug (male) / 2.92mm plug (male) Straight Adaptor DC-40 GHz, VSWR ≤ 1.15

AD-V1K15A / 9XX-9XX



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

1.85mm according to	IEC 61169-32
2.92mm according to	IEC 61169-35

Electrical Data

Impedance	50 Ω
Frequency	DC to 40 GHz
VSWR (Return Loss)	≤ 1.15 (≥ 23.1 dB)
Insertion Loss	≤ 0.05 x √F (GHz) dB
Insulation resistance	≥ 5 GΩ
Test voltage	500 V rms
Working voltage	150 V rms
RF-leakage	≥ 100 dB up to 1 GHz

Material And Plating

Piece Parts (1.85mm)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 pinch (Non-magnetic nickel-phosphorus underplating, 80 pinch)
Body	Stainless Steel	Passivated
Insulator	PEI	Passivated
Coupling nut	Stainless Steel	Passivated
Piece Parts (2.92mm)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 pinch (Non-magnetic nickel-phosphorus underplating, 80 pinch)
Body	Stainless Steel	Passivated
Insulator	PEI	Passivated
Coupling nut	Stainless Steel	Passivated

1.85mm plug (male) / 2.92mm plug (male) Straight Adaptor DC-40 GHz, VSWR ≤ 1.15

AD-V1K15A / 9XX-9XX

Mechanical Data

Coupling mechanisms	1.85mm side	2.92mm side
Mating cycles	Screw-lock	Screw-lock
Center contact captivation	≥ 500	≥ 500
Coupling test torque	≥ 20 N	≥ 20 N
Recommended torque	1.65 Nm	1.70 Nm
	0.80 Nm to 1.10 Nm	0.80 Nm to 1.10 Nm

Environmental Data

Temperature Range	-55°C to +165°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100