


BNC plug (male) / BNC jack (female)
T-Adaptor 1 plug , 2 jacks DC-10 GHz

ADT-B2B1B25B/93-133-93



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

according to

IEC 60169-8; MIL-STD-348B/301

Electrical Data

Impedance	50 Ω
Frequency	DC to 10 GHz
Insulation resistance	≤ 5 GΩ
Center contact resistance	≤ 1.5 mΩ
Outer contact resistance	≤ 1 mΩ
Test voltage	1500 V rms
Working voltage	400 V rms
Power handling	≤ 80 W @ 2 GHz

Material And Plating

Piece Parts (BNC - male)	Material	Plating
Centre contact	Brass	Gold plating, 3 μinch(Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Brass	Nickel
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Brass	Nickel
Piece Parts (BNC - female)	Material	Plating
Centre contact	Beryllium Copper	Gold plating, 3 μinch(Non-magnetic nickel-phosphorus underplating, 80 μinch)
Body	Brass	Nickel
Insulator	PTFE	

BNC plug (male) / BNC jack (female)
T-Adaptor 1 plug , 2 jacks DC-10 GHz

ADT-B2B1B25B/93-133-93

Mechanical Data

Coupling mechanisms	Bayonet-lock
Mating cycles	≥ 500
Center contact captivation: axial	≥ 15 N

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. B
Shock	MIL-STD-202, Meth. 213, Cond. G
Moisture resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100