




SMA plug (male) to N plug (male) Miter Right Angle Adapter DC-12 GHz VSWR1.25

ASL-A1N15A / 111-144



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

SMA according to

IEC 60169-15;CECC 22110; MIL-PRF-39012 SMA; MIL-STD-348/310

N according to

IEC 60169-16;MIL-STD-348/304;CECC 22 210

Electrical Data

Impedance

50 Ω

Frequency

DC to 12 GHz

VSWR

≤ 1.25 (≥ 19.08 dB)

Insertion loss

N/A

Insulation resistance

≥ 5 G Ω

Center contact resistance

≤ 3 m Ω , SMA side

≤ 1 m Ω , N side

Outer contact resistance

≤ 2 m Ω , SMA side

≤ 0.25 m Ω , N side

Test voltage

1000 V rms

Working voltage

480 V rms

Power handling (at 20 °C, sea level, VSWR 1.0)

≤ 200 W @ 2 GHz

RF-leakage

≥ 100 dB up to 1 GHz

Material And Plating

Piece Parts (SMA)	Material	Plating
Centre contact	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Piece Parts (N)	Material	Plating
Centre contact	Brass	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Brass	Copper-Tin-Zinc Alloy
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling nut	Brass	Copper-Tin-Zinc Alloy

The facts and figures herein are carefully compiled to the best of our knowledge, but they are intended for general informational purposes only. In the effort to improve our products, we reserve the right to make changes judged to be necessary.

Rev.:-

Date:

FEB/10/2025

Rosnol RF/Microwave Technology Co., Ltd.

www.rosnol.com; info@rosnol.com

Phone: +886-3-463-5095 / Fax: +886-3-463-5952

N-CAGE Code: SFKK0 / ISO9001 Certified

Page

1/2

SMA plug (male) to N plug (male) Miter Right Angle Adapter DC-12 GHz VSWR1.25

ASL-A1N15A / 111-144

Mechanical Data

	SMA side	N side
Coupling mechanisms	Screw-lock	Screw-lock
Mating cycles	min. 500	min. 500
Center contact captivation: axial	≥ 28 N	≥ 28 N
Coupling test torque	max. 1.7 Nm	max. 1.7 Nm
Recommended torque	0.8 Nm to 1.1 Nm	0.7 Nm to 1.1 Nm

Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Meth. 107, Cond. B
Corrosion	MIL-STD-202, Meth. 101, Cond. B
Vibration	MIL-STD-202, Meth. 204, Cond. D
Shock	MIL-STD-202, Meth. 213, Cond. I
Moisture resistance	MIL-STD-202, Meth. 106
RoHS	compliant

Packing

Single or 100