


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	DEC/09/2025	

Rosnol P/N	Length (mm)	
A1C50-RG142-A1C50-500A/4G	500	
A1C50-RG142-A1C50-1000A/4G	1000	
A1C50-RG142-A1C50-3000A/4G	3000	
A1C50-RG142-A1C50-5000A/4G	5000	
Frequency	VSWR Max.	Insertion Loss Max. (dB)
4 GHz	1.25	$\leq 0.000945 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f}$



CUSTOMER'S APPROVAL

Department or company's stamp

Name:

Date:

Copy and send back to ROSNOL CORPORATION BEFORE:

NOTES:

- 1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- 2) MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 4 GHz
A1C50-RG142-A1C50-XXX/4G
WW/YY - SERIAL NUMBER
- 3) ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

4	LABEL HEAT SHRINK TUBE	HST-W-D6-125C	1	EA	DIMENSION ARE IN MM [INCH] TOLERANCES DECIMALS .X ± 6.35 [.250"] .XX ± 3.18 [.125"] .XXX ± 1.52 [.060"] DEGREES X° ± 1°	CUSTOMER	REV	UNIT
3	HEAT SHRINK TUBE	HST-B-D8-125C	2X 30	mm		-	-	mm [inch]
2	CABLE	RG-142B/U Cable	See table above	mm		APPROVED	DATE	
1	SMA CRIMP PLUG	SMA1C50-G142C/133	2	EA		DRAWN	DATE	
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M				

ROSNOL 
RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
SMA Plug (Male) to SMA Plug (Male)
XXX Meter Cable Assembly for RG-142B/U Cable
DRAWING NO.
A1C50-RG142-A1C50-XXX/4G