


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N		Length (mm)
B1E50-EF402-A1E50-1000A/4G		1000
Frequency	VSWR Max.	Insertion Loss Max.
4 GHz	1,25	$\leq 0.000738 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f \text{ (dB)}}$

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	FEB/3/2025	



CUSTOMER'S APPROVAL

Department or
company's stamp

Name:

Date:

Copy and send back to
ROSNOL CORPORATION BEFORE:

NOTES:

- CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 4 GHz
B1E50-EF402-A1E50-1000A/4G
WW/YY SERIAL NUMBER
- ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES : $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

5	LABEL HEAT SHRINK TUBE	HST-W-D6-125C	1	EA
4	HEAT SHRINK TUBE	HST-B-D6-125C	2X 30	mm
3	CABLE	ROSNOL EF402 CABLE	1000	mm
2	SMA SOLDER PLUG	SMA1E50-EZ141A/91X	1	EA
1	BNC SOLDER PLUG	BNC1E50-0141A/144	1	EA
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M

DIMENSION ARE IN MM [INCH]

TOLERANCES

DECIMALS
.X ± 6.35 [.250"]
.XX ± 3.18 [.125"]
.XXX ± 1.52 [.060"]
DEGREES
X° $\pm 1^\circ$

CUSTOMER

REV

-

UNIT

mm [inch]

APPROVED

DATE

DRAWN

DATE

ROSNOL

RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0



TITLE

BNC Plug (Male) to SMA Plug (Male)
1 Meter Cable Assembly for EF402 Cable

DRAWING NO.

B1E50-EF402-A1E50-1000A/4G