


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N	Length (mm)	
B1E50-EF402-B1E50-1000A/3G	1000	
Frequency	VSWR Max.	Insertion Loss Max.
3 GHz	1.25	$\leq 0.000738 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f(\text{GHz})}$

SPECIFICATION CONTROL DRAWING

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	FEB/3/2025	



NOTES:

- 1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- 2) MARKING DETAILS IF NOT SPECIAL MARKING TEXT:

ROSNOL DC- 3 GHz
B1E50-EF402-B1E50-1000A/3G
WW/YY SERIAL NUMBER

- 3) ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES : $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

CUSTOMER'S APPROVAL	
Department or company's stamp	
Name:	
Date:	
Copy and send back to ROSNOL CORPORATION BEFORE:	

4	LABEL HEAT SHRINK TUBE	HST-W-D6-125C	1	EA	DIMENSION ARE IN MM [INCH] TOLERANCES DECIMALS .X ± 6.35 [.250"] .XX ± 3.18 [.125"] .XXX ± 1.52 [.060"] DEGREES X° ± 1°	CUSTOMER	REV -	UNIT mm [inch]
3	HEAT SHRINK TUBE	HST-B-D6-125C	2X 30	mm				
2	CABLE	ROSNOL EF402 CABLE	1000	mm				
1	BNC SOLDER PLUG	BNC1E50-0141A/144	2	EA				
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M				

ROSNOL 
RF/Microwave Technology
www.rosnol.com
info@rosnol.com

N-CAGE Code: SFKK0

TITLE
BNC Plug (Male) to BNC Plug (Male)
1 Meter Cable Assembly for EF402 Cable

DRAWING NO.
B1E50-EF402-B1E50-1000A/3G