
INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

SPECIFICATION CONTROL DRAWING

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
–	INITIAL RELEASE	OCT/01/2025	

Rosnol P/N		Length (mm)
K1K50-MP420A-K1K50-500A/40G		500
Frequency	**VSWR Max.**	**Insertion Loss Max. (dB)**
40 GHz	1.25	≤ 0.00285(dB/mm) * L (mm) + 0.15* √f



CUSTOMER'S APPROVAL

Department or company's stamp

Name:

Date:

Copy and send back to ROSNOL CORPORATION BEFORE:

NOTES:
1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
2) MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
   ROSNOL DC - 40 GHz
   K1K50-MP420A-K1K50-500A/40G
   WWYY-SERIAL NUMBER
3) ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
   ±3 mm FOR L<=300mm ; ±1% FOR L >300mm

NO.	DESCRIPTION	PARTS NO.	QTY.	U/M
4	LABEL HEAT SHRINK TUBE	HST-W-D6-125C	1	EA
3	HEAT SHRINK TUBE	HST-B-D6.4-125C-G	2X 50	mm
2	CABLE	ROSNOL MP420A Cable	500	mm
1	2.92mm SOLDER CLAMP PLUG	K1K50-MP420A/9XX	2	EA

DIMENSION ARE IN MM [INCH]

TOLERANCES

DECIMALS
.X ± 6.35 [.250"]
.XX ± 3.18 [.125"]
.XXX ± 1.52 [.060"]
DEGREES
X° ± 1°

CUSTOMER | REV – | UNIT mm [inch]

APPROVED | DATE

DRAWN | DATE

ROSNOL
RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
2.92mm Plug (Male) to 2.92mm Plug (Male)
0.5 Meter Cable Assembly for MP420A Cable

DRAWING NO.
K1K50-MP420A-K1K50-500A/40G