
INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

SPECIFICATION CONTROL DRAWING

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
–	INITIAL RELEASE	FEB/26/2024	

Rosnol P/N		Length (mm)
N1E50-RSF141FEP-T1E50-500A/6G		500
N1E50-RSF141FEP-T1E50-1000A/6G		1000
N1E50-RSF141FEP-T1E50-2000A/6G		2000
Frequency	**VSWR Max.**	**Insertion Loss Max.**
6 GHz	1.25	≤ 0.0014 (dB/mm) * L (mm) + 0.1 (dB)



NO.	DESCRIPTION	PARTS NO.	QTY.	U/M
5	LABEL HEAT SHRINK TUBE	HST-W-D4-125C-G	1	EA
4	HEAT SHRINK TUBE	HST-B-D6.4-125C	2X 20	mm
3	CABLE	ROSNOL RSF141FEP	XXX	mm
2	TNC SOLDER PLUG	TNC1E50-0141A/133	1	EA
1	N SOLDER PLUG	N1E50-EZ141A/91X	1	EA

DIMENSION ARE IN MM [INCH]

TOLERANCES

DECIMALS
.X ± 6.35 [.250"]
.XX ± 3.18 [.125"]
.XXX ± 1.52 [.060"]
DEGREES
X° ± 1°

REV –

UNIT mm [inch]

DATE

DRAWN DATE

ROSNOL
RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE

N Plug (Male) to TNC Plug (Male)
XXX Meter Cable Assembly for RSF141FEP Cable

DRAWING NO.

N1E50-RSF141FEP-T1E50-XXXA/6G