
INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

SPECIFICATION CONTROL DRAWING

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
–	INITIAL RELEASE	-	

Rosnol P/N	Length (mm)	Insertion Loss Max. (dB)
PC1K50-MPUL503A-PC1K50-1000A/ 26.5G	1000	≤ 2.23
Frequency : 26.5 GHz	**VSWR Max. : 1.25**	



NOTES:
1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
2) MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
   ROSNOL DC-26.5 GHz
   PC1K50-MPUL503A-PC1K50-1000A/26.5G
   WW/YY - SERIAL NUMBER
3) ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
   ±3 mm FOR L<=300mm ; ±1% FOR L >300mm

CUSTOMER'S APPROVAL

Department or company's stamp

Name:

Date:

Copy and send back to ROSNOL CORPORATION BEFORE:

NO.	DESCRIPTION	PARTS NO.	QTY.	U/M
4	LABEL HEAT SHRINK TUBE	HST-W-D6-125C	1	EA
3	HEAT SHRINK TUBE	HST-B-D6.4-125C-G	2X 50	mm
2	CABLE	ROSNOL MPUL503A Cable	1000	mm
1	3.5 mm SOLDER CLAMP PLUG	PC1K50-MPUL503A/9XX	2	EA

DIMENSION ARE IN MM [INCH]

TOLERANCES

DECIMALS
.X ± 6.35 [.250"]
.XX ± 3.18 [.125"]
.XXX ± 1.52 [.060"]
DEGREES
X° ± 1°

CUSTOMER	REV	UNIT
-	–	mm [inch]

APPROVED	DATE
–	-

DRAWN	DATE
–	-

ROSNOL
RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
3.5mm Plug (Male) to 3.5mm Plug (Male)
1 Meter Cable Assembly for MPUL503A Cable

DRAWING NO.
PC1K50-MPUL503A-PC1K50-1000A/26.5G