


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N	Length (mm)	
PCN1K50-MP790A-A2K50-2500A/18G	2500	
Frequency	VSWR Max.	Insertion Loss Max. (dB)
18 GHz	1.25	$\leq 0.00068 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f}$

SPECIFICATION CONTROL DRAWING

REVISION			
REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	JUN/09/2025	



CUSTOMER'S APPROVAL

Department or company's stamp

Name:

Date:

Copy and send back to ROSNOL CORPORATION BEFORE:

NOTES:

- 1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- 2) MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 18 GHz
PCN1K50-MP790A-A2K50-2500A/18G
WW/YY - SERIAL NUMBER
- 3) ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm FOR } L \leq 300 \text{ mm ; } \pm 1\% \text{ FOR } L > 300 \text{ mm}$

5	LABEL HEAT SHRINK TUBE	HST-W-D12-125C	1	EA
4	HEAT SHRINK TUBE	HST-B-D12.7-125C-G	2X 50	mm
3	CABLE	ROSNOL MP790A Cable	2500	mm
2	SMA Jack (Female)	SMA2K50-MP790A/9X	1	EA
1	Precision N Plug (Male)	PCN1K50-MP790A/9XX	1	EA
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M

DIMENSION ARE IN MM [INCH]	CUSTOMER	REV	UNIT mm [inch]
TOLERANCES			
DECIMALS .X ± 6.35 [.250"] .XX ± 3.18 [.125"] .XXX ± 1.52 [.060"]	APPROVED	DATE	
DEGREES X° ± 1°	DRAWN	DATE	

ROSNOL 
RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
Precision N Plug (Male) to SMA Jack (Female)
2.5 Meter Cable Assembly for MP790A Cable
DRAWING NO.
PCN1K50-MP790A-A2K50-2500A/18G