


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N		Length (mm)
PCN1K50-MP841A-PCN1K50-2500A/18G		2500
Frequency	VSWR Max.	Insertion Loss Max.
18 GHz	1.25	$\leq 0.00087 \text{ (dB/mm)} * L \text{ (mm)} + 0.1 * \sqrt{f \text{ (dB)}}$

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	NOV/26/2024	



CUSTOMER'S APPROVAL

Department or
company's stamp

Name:

Date:

Copy and send back to
ROSNOL CORPORATION BEFORE:

NOTES:

- CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 18 GHz
PCN1K50-MP841A-PCN1K50-2500A/18G
WW/YY SERIAL NUMBER
- ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

4	LABEL HEAT SHRINK TUBE	HST-W-D10-125C	1	EA	DIMENSION ARE IN MM [INCH] TOLERANCES DECIMALS .X ± 6.35 [.250"] .XX ± 3.18 [.125"] .XXX ± 1.52 [.060"] DEGREES X° $\pm 1^\circ$	CUSTOMER	REV	UNIT
3	HEAT SHRINK TUBE	HST-B-D12.7-125C-G	2X 50	mm			-	mm [inch]
2	CABLE	Rosnol MP841A Cable	2500	mm		APPROVED	DATE	
1	Precision N SOLDER CLAMP PLUG	PCN1K50-0630A/1XX	2	EA		DRAWN	DATE	
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M				

ROSNOL



RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE

Precision N Plug (Male) to Precision N Plug (Male)
2.5 Meter Cable Assembly for MP841A Cable

DRAWING NO.

PCN1K50-MP841A-PCN1K50-2500A/18G