


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N		Length (mm)
PCT1K50-MT610A-A1K50-1200A/18G_W4109		1200
Frequency	VSWR Max.	Insertion Loss Max. (dB)
18 GHz	1.4	$\leq 0.00118 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f}$

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	JUL/3/2025	



CUSTOMER'S APPROVAL

Department or
company's stamp

Name:

Date:

Copy and send back to
ROSNOL CORPORATION BEFORE:

NOTES:

- CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 18 GHz
PCT1K50-MT610A-A1K50-1200A/18G_W4109
WW/YY - SERIAL NUMBER
- ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

5	LABEL HEAT SHRINK TUBE	HST-W-D12-125C	1	EA
4	HEAT SHRINK TUBE	HST-B-D19.1-125C-G	2X 60	mm
3	CABLE	ROSNOL MT610A Cable	1200	mm
2	SMA SOLDER CLAMP PLUG	SMA1K50-MT610A/9XX	1	EA
1	Precision TNC SOLDER CLAMP PLUG	PCT1K50-MT610A/9XX	1	EA
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M

DIMENSION ARE IN MM [INCH]		CUSTOMER	REV	UNIT
			-	mm [inch]
TOLERANCES		APPROVED		
DECIMALS		DATE		
.X ± 6.35 [.250"]				
.XX ± 3.18 [.125"]				
.XXX ± 1.52 [.060"]				
DEGREES		DRAWN		
X° $\pm 1^\circ$		DATE		

ROSNOL

RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFFKK0

TITLE
Precision TNC Plug (Male) to SMA Plug (Male)
1.2 Meter Cable Assembly for MT610A Cable

DRAWING NO.
PCT1K50-MT610A-A1K50-1200A/18G_W4109