


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N		Length (mm)
PCT1K50-MT902A-A1K50-5500A/18G		5500
Frequency	VSWR Max.	Insertion Loss Max. (dB)
18 GHz	1.4	$\leq 0.000657 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f}$

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	JUL/3/2025	



CUSTOMER'S APPROVAL

Department or company's stamp

Name:

Date:

Copy and send back to ROSNOL CORPORATION BEFORE:

NOTES:

- 1) CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- 2) MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 18 GHz
PCT1K50-MT902A-A1K50-5500A/18G_W4315
WW/YY - SERIAL NUMBER
- 3) ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

5	LABEL HEAT SHRINK TUBE	HST-W-D12-125C	1	EA
4	HEAT SHRINK TUBE	HST-B-D16-125C-G	2X 60	mm
3	CABLE	Rosnol MT902A Cable	5500	mm
2	SMA SOLDER CLAMP PLUG	SMA1K50-MT902A/9XX	1	EA
1	PRECISION TNC SOLDER CLAMP PLUG	PCT1K50-MT902B/9XX	1	EA
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M

DIMENSION ARE IN MM [INCH]	CUSTOMER	REV	UNIT
TOLERANCES		—	mm [inch]
	APPROVED		
	DATE		
	DRAWN		
	DATE		
DECIMALS			
.X ± 6.35 [.250"]			
.XX ± 3.18 [.125"]			
.XXX ± 1.52 [.060"]			
DEGREES			
X° ± 1°			

ROSNOL 

RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
Precision TNC Plug (Male) to SMA Plug (Male)
5.5 Meter Cable Assembly for MT902A Cable

DRAWING NO.
PCT1K50-MT902A-A1K50-5500A/18G