


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N		Length (mm)
Q2K50-VNA50A-NMQ2K50-1000A /50G		1000
Frequency	VSWR Max.	Insertion Loss Max. (dB)
50 GHz	1.25	$\leq 0.0039 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f}$

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	NOV/05/2025	



CUSTOMER'S APPROVAL

Department or
company's stamp

Name:

Date:

Copy and send back to
ROSNOL CORPORATION BEFORE:

NOTES:

- CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 50 GHz
Q2K50-VNA50A-NMQ2K50-1000A/50G
WW/YY - SERIAL NUMBER
- ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

4	LABEL HEAT SHRINK TUBE	HST-W-D20-125C	1	EA	DIMENSION ARE IN MM [INCH]	CUSTOMER	REV	UNIT
3	CABLE	ROSNOL VNA50A Cable	1000	mm	TOLERANCES DECIMALS .X ± 6.35 [.250"] .XX ± 3.18 [.125"] .XXX ± 1.52 [.060"] DEGREES X° ± 1°	DATE		mm [inch]
2	Ruggedized NMD 2.4mm Jack	NMQ2K50-VNA50A/9XX	1	EA		DATE		
1	2.4mm Solder Clamp Jack	Q2K50-VNA50A/9X	1	EA				
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M		DATE		

ROSNOL

RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
2.4mm Jack (Female) to NMD 2.4mm Jack (Female)
1 Meter Cable Assembly for VNA50A Cable

DRAWING NO.
Q2K50-VNA50A-NMQ2K50-1000A/50G