


INFORMATION CONTAINED WITHIN THIS ROSNOL RF/MICROWAVE TECHNOLOGY CORP. DOCUMENT IS CONSIDERED PROPRIETARY AND IS THE PROPERTY OF ROSNOL RF/MICROWAVE TECHNOLOGY CORP.

Rosnol P/N		Length (mm)
SC1K50-MT902A-N1K50-1500A/6G		1500
Frequency	VSWR Max.	Insertion Loss Max. (dB)
6 GHz	1.3	$\leq 0.000365 \text{ (dB/mm)} * L \text{ (mm)} + 0.15 * \sqrt{f}$

SPECIFICATION CONTROL DRAWING

REVISION

REV.	DESCRIPTION	DATE	APPROVED
-	INITIAL RELEASE	JUL/3/2025	



CUSTOMER'S APPROVAL

Department or
company's stamp

Name:

Date:

Copy and send back to
ROSNOL CORPORATION BEFORE:

NOTES:

- CONNECTORS ASSEMBLED PER MANUFACTURERS INSTRUCTIONS.
- MARKING DETAILS IF NOT SPECIAL MARKING TEXT:
ROSNOL DC- 6 GHz
SC1K50-MT902A-N1K50-1500A/6G_W4603
WW/YY - SERIAL NUMBER
- ALL DIMENSIONS ARE IN MM ; LENGTH TOLERANCES :
 $\pm 3 \text{ mm}$ FOR $L \leq 300 \text{ mm}$; $\pm 1\%$ FOR $L > 300 \text{ mm}$

5	LABEL HEAT SHRINK TUBE	HST-W-D12-125C	1	EA
4	HEAT SHRINK TUBE	HST-B-D16-125C-G	2X 60	mm
3	CABLE	Rosnol MT902A Cable	1500	mm
2	N SOLDER CLAMP PLUG	N1K50-MT902A/9XX	1	EA
1	SC SOLDER CLAMP PLUG	SC1K50-MT902A/9XX	1	EA
NO.	DESCRIPTION	PARTS NO.	QTY.	U/M

DIMENSION ARE IN MM [INCH]	CUSTOMER	REV	UNIT
TOLERANCES		—	mm [inch]
	APPROVED		
	DATE		
	DRAWN		
DATE			
DECIMALS			
.X ± 6.35 [.250"]			
.XX ± 3.18 [.125"]			
.XXX ± 1.52 [.060"]			
DEGREES			
X° ± 1°			

ROSNOL 
RF/Microwave Technology
www.rosnol.com
info@rosnol.com
N-CAGE Code: SFKK0

TITLE
SC Plug (Male) to N Plug (Male)
1.5 Meter Cable Assembly for MT902A Cable

DRAWING NO.
SC1K50-MT902A-N1K50-1500A/6G