


SMA Plug (Male) Termination DC-10 GHz; 1Watt; VSWR1.2

T-A15-10G1WA / 9XX



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

Interface

According to

IEC 60169-15, MIL-STD-348B/310

Electrical Data

Impedance

50 Ω

Frequency

DC to 10 GHz

VSWR (Return Loss)

≤ 1.2 (≥ 20.83 dB)

Average power (at 25°C)

1 W

Material And Plating

Piece Parts (BNC)	Material	Plating
Centre Contact	Beryllium Copper	Gold plating, 3 μ inch (Non-magnetic nickel-phosphorus underplating, 80 μ inch)
Body	Stainless Steel	Passivate
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling Nut	Stainless Steel	Passivate

SMA Plug (Male) Termination DC-10 GHz; 1Watt; VSWR1.2

T-A15-10G1WA / 9XX

Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500
Coupling Nut Retention	N/A
Center Contact Captivation	≥ 20 N
Coupling Test Torque	1.70 Nm max.
Recommended Torque	0.9 Nm

Environmental Data

Temperature Range	-55°C to +125°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition D
Shock	MIL-STD-202, Method 213, Condition I
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

Packing

Single or 100