


# TNC Plug (Male) Termination With Chain

## DC-6 GHz; 2Watt; VSWR1.2

### T-T15-6G2WB-88.9 / 9XX



All dimensions are in mm [inch]

Tolerances according to DIN ISO 2768-mH

#### Interface

According to

IEC 61169-17;CECC 22 200;MIL-PRF-39012;TNC-Interface MIL-STD 348/313

#### Electrical Data

Impedance

50 Ω

Frequency

DC to 6 GHz

VSWR (Return Loss)

≤ 1.2 (≥ 20.83 dB)

Average power (at 25°C)

2 W

≤ 1 W, derated linearity by 0.01 W/K

#### Material And Plating

Piece Parts	Material	Plating
Centre Contact	Beryllium Copper	Gold plating (Non-magnetic nickel-phosphorus underplating)
Body	Stainless Steel	Passivated
Insulator	PTFE	
Gasket	Silicone Rubber	
Coupling Nut	Stainless Steel	Passivated
Chain	Stainless Steel	Passivated

## TNC Plug (Male) Termination With Chain DC-6 GHz; 2Watt; VSWR1.2

### T-T15-6G2WB-88.9 / 9XX

#### Mechanical Data

Coupling mechanisms	Screw-lock
Mating Cycles	≥ 500
Center Contact Captivation:axial	≥ 27 N
Coupling Test Torque	1.70 Nm max.
Recommended Torque	0.46 Nm to 0.69 Nm

#### Environmental Data

Temperature Range	-65°C to +165°C
Thermal shock	MIL-STD-202, Method 107, Condition B
Corrosion	MIL-STD-202, Method 101, Condition B
Vibration	MIL-STD-202, Method 204, Condition B
Shock	MIL-STD-202, Method 213, Condition G
Moisture Resistance	MIL-STD-202, Method 106
RoHS	compliant

#### Packing

Single or 100