

# Technical Data Sheet

# Crimp Insert For

RG-8/RG-11/RG-174/RG-179/RG-213/RG-214/LMR 400/RNL-400

CI-L33KA



| 1.7              | laterial |  |
|------------------|----------|--|
| $\Lambda \prime$ | aterial  |  |
| 1 7              | ıarenai  |  |

Material Tooling parts Black oxide and hardened Carbon steel (SKD11) Crimp insert

## Hex Cavity Dimensions

 $2.54 mm \; [0.100 in], \; 3.25 mm \; [0.128 in], \; 10.90 mm \; [0.429 in]$ 

#### Mechanical Data

Weight 0.047 kg

#### Recommended for these cables

RG-8, RG-11, RG-174, RG-179, RG-213, RG-214, LMR 400, RNL-400

## Tooling

CT-L3 Crimping tool

| The facts and figures herein are carefully compiled to the best of our      |
|---|
| knowledge, but they are intended for general informational purposes only.   |
| In the effort to improve our products, we reserve the right to make changes |
| judged to be necessary.   |

| I I/C/ | Rosnol RF/Microwave Technology Co., Ltd.<br>www.rosnol.com; info@rosnol.com |
|--------|---|
|        | Phone: +886-3-463-5095 / Fax: +886-3-463-5952                               |